

CLAIMS LISTING – MARKED-UP VERSION

Appl. No.: 10/648,301
Filing Date: 08/27/2003
Applicant: KOMARECHKA, Robert G.
5 Art Unit: 2672
Examiner: WOODS, Eric V.

CLAIM 1 (currently amended)

A method of displaying three-dimensional vector orientations and intensities on a
10 two-dimensional surface comprising:

i. the steps of:

a. Collecting said three-dimensional information,

b. Transforming said three-dimensional Cartesian information to
spherical co-ordinates,

15 c. Assigning a predetermined display pattern to said spherical co-
ordinates, and

d. ~~Plotting~~ Illustrating a visual rendition of said predetermined
display pattern on said two-dimensional ~~display~~ surface,

ii. a step of calibrating said three-dimensional information,

20 iii. a method for rapidly and visually determining the orientation and
intensity of ~~3D-3 dimensional~~ vectors within a vector field,

iv. a method of rapidly visually correlating ~~3D-3 dimensional~~ vectors of a
common orientation and intensity,

v. a method for rapidly isolating specific vector orientations and
25 determining their exact co-ordinate location,

- vi. a method for quickly displaying a scattergram of orientations and intensities within a specified study area or volume,
- vii. a method of enhancing the visual discrimination of subtle variation in vector orientation and intensity,
- 5 viii. a methodology of presenting data that allows for the ability to incorporate rapid color change to the pixelated or voxelated image, allowing for a time varying display hence providing the user the ability to visualize slow time, real time or fast time visualization of the individual vector orientations and intensities within a dynamically
- 10 changing vector field, field.

CLAIM 2 (currently amended)

The method of Claim 1 wherein said step of -illustrating a visual rendition of vector orientations and intensities ~~plotting~~ comprises the steps of:

- i. transmitting said predetermined display pattern to a
- 15 ~~plotter~~ visualization device,
- ii. displaying said spherical co-ordinates corresponding to said display pattern on said two-dimensional display,

CLAIM 3 (original)

20 The method of Claim 1 wherein the tri-axial data measurement or its gradient is selected from the group consisting of:

- i. geomagnetic,
- ii. fluid flow,

- iii. gravitational,
- iv. surface, and
- v. electro-magnetic field (inclusive of polarimetric orientation),

5 **CLAIM 4 (currently amended)**

The tri-axial data measurement of the method of Claims 1 or 3 wherein, said data measurement is collected by means selected from the group consisting of:

- i. airborne,
- ii. ground,
- 10 iii. borehole, and
- iv. submarine,

CLAIM 5 (currently amended)

15 The method of Claims 1, 2 ~~and or~~ 3 wherein the potential use exists for visualization of the orientation and intensity of the remanent~~remnant~~ vector for events occurring within the study area over geologic times of differing orientations of the earth's magnetic field, allowing for the ability to:

- i) discriminate different ages of intrusive rock, even if the rock types are identical in composition and magnetic susceptibility,
- 20 ii) determine the extent of later thermal aureoles above the Currie or Ne'el temperature of the constituent ferromagnetic minerals of the rock being measured,
- iii) discriminate some areas of folding and faulting,